OCPP 1.6 Full Certificate



Certificate holder:	EV-Box B.V.
Certificate number:	OCA.0016.0005.CS
Product type:	Charging Station
Product designation:	ELVI Socket, OCPP Software version: G4P0421BE421v0 (Release version), P0417BE417v11 (Test version)
Certification date:	December 19, 2019

This certificate attests that the above mentioned product successfully completed certification testing in conformance with the reference specification OCPP 1.6 – Edition 2 with OCPP 1.6 Errata sheet (v4.0 Release, 2019-10-23). The optional features of the protocol are also covered by this certification.

Test cases have been performed as described in the test report referred to below. The results and remarks can be found in the complete test report.

Applied tests	Performed by / on	Document evidence
Conformance testing according to the test specification referenced by the test report	DNV GL Lab Arnhem, NL, December 19, 2019	DNVGL_20191219_Test Report_EV- Box_V104

The Protocol Implementation Conformance Statement in the Annex is an integral part of this certificate. This certificate is valid from the Certification Date specified above. This certificate is only applicable to the product designation described above and permits the use of the OCPP logo as laid down in the OCA certification logo license agreement on this product only.

This certificate shall neither be tendered nor accepted by any party as a guarantee covering quality of a product which includes OCPP. The Open Charge Alliance, and/or its agents, including, inter-alia, test laboratories, disclaim liability for any damages or losses incurred by the certified company or by any other party resulting from reliance on the results of OCPP certification testing.

For the Open Charge Alliance:

ONOPH CARON Chairman

Authenticity of this certificate can be verified at www.openchargealliance.org

Abstract of test report

Test Result Summary

Test Result Summury				
Test Report OCPP 1.6 Certification				
st laboratory: DNV GL Netherlands B.V.				
Location:	Arnhem, Netherlands			
Test Report Reference:	DNVGL_20191219_Test Report_EV-Box_V104			
Vendor name:	EV-Box B.V.			
Device Under Test:	Charging Stati	on		
Communication:	JSON			
OCPP Software version:	P0417BE417v1	1		
Test Result Summar	y for the ce	rtified functionalities		
Functionalities	OCPP 1.6 Certification Test Results	Description		
Core	Pass	Basic Charging Station functionality for booting, authorization (incl. cache if available), configuration, transactions, remote control.		
Optional functionalities				
Firmware Management	Pass	Support for (remote) firmware update management and diagnostic log file download.		
Smart Charging	Pass	Support for Smart Charging (all profile types, including stacking), to control charging.		
Reservation	Pass	Support for reservation of a connector of a Charging Station.		
Local Authorization List Management	Pass	Features to manage a local list in the charging station containing authorization data for whitelisting users.		
Remote Trigger	Pass	Support for remotely triggering messages that originate from a Charging Station. This can be used for resending messages or for getting the latest information from the Charging Station.		





Performance Measurement Results

Performance Measurement Results				
Name	e PICS value Measured value Description			
OCPP triggered function timeout:	60 seconds	43 seconds	The response time for when waiting for an OCPP function with its corresponding request message. (Firmware update, Diagnostics and Reboot are excluded from this measurement.)	
OCPP response timeout:	10 seconds	8 seconds	The response time for when waiting for an OCPP response message.	
Response time RemoteStartTransaction:	10 seconds	3 seconds	The response time for the RemoteStartTransaction message.	

Test Configuration

lest Configuration				
Vendor	EV Box B.V.			
DUT / SUT	Charging Station			
Communication	JSON			
Туре	ELVI Socket			
OCPP Software version	P0417BE417v11			
OCTT version OCTT 1.6 v1.3				

Hardware feature set				
Feature	Configuration			
Socket(s) / connector(s)	Singe			
Fixed cable No				
Communication technology	WiFi / Mobile network			
RFID readers Single				

Non-OCPP Charge Point Configuration			
Configuration key Value			
evb_ServerURL	ws://194.53.239.94:2404/ocpp/		

All other relevant limits and non-OCPP settings that are relevant for the test laboratory and for the correct functioning of the CSMS:			
Limit / setting Value			
Device supports sending milliseconds in timestamps.	No		

Page 2 from 4



OCPP Charging Station Configuration			
Configuration key	Value		
AllowOfflineTxForUnknownId	true,false		
AuthorizationCacheEnabled	true,false		
AuthorizeRemoteTxRequests	true,false		
BlinkRepeat	not supported		
ClockAlignedDataInterval	0		
ConnectionTimeOut	60		
ConnectorPhaseRotation	0.Unknown,1.RST		
ConnectorPhaseRotationMaxLength	not supported 21(default value)		
GetConfigurationMaxKeys	1		
HeartbeatInterval	60 sec (minimum)		
LightIntensity	0-100, (default 50)		
LocalAuthorizeOffline	true,false		
LocalPreAuthorize	true,false		
MaxEnergyOnInvalidId	not supported		
MessageTimeout	60 sec		
MeterValuesAlignedData	Energy.Active.Import.Register		
MeterValuesAlignedDataMaxLength	11		
MeterValuesAlignedDataMaxLength	<optional></optional>		
MeterValuesSampledData	Energy.Active.Import.Register		
MeterValuesSampledDataMaxLength	11		
MeterValueSampleInterval	60 sec (minimum)		
MinimumStatusDuration	<optional></optional>		
NumberOfConnectors			
	-		
ResetRetries	<configurable></configurable>		
StopTransactionMaxMeterValues	<optional></optional>		
StopTransactionOnEVSideDisconnect	true,false		
StopTransactionOnInvalidId	true,false		
StopTxnAlignedData	<configurable></configurable>		
StopTxnAlignedDataMaxLength	<optional></optional>		
StopTxnSampledData			
StopTxnSampledDataMaxLength	<optional></optional>		
	Core, FirmwareManagement,		
	LocalAuthListManagement,		
	SmartCharging,RemoteTrigger,		
SupportedFeatureProfiles	Reservation		
SupportedFeatureProfilesMaxLength	6		
TransactionMessageAttempts	3		
TransactionMessageRetryInterval	10s		
UnlockConnectorOnEVSideDisconnect	true,false		
WebSocketPingInterval	No limit (60 sec default)		
LocalAuthListEnabled	true,false		
LocalAuthListMaxLength	250		
SendLocalListMaxLength	25		
ReserveConnectorZeroSupported	WAAR		
ChargeProfileMaxStackLevel	2		
ChargingScheduleAllowedChargingRateUnit	"Current, Power"		
ChargingScheduleMaxPeriods	25		
ConnectorSwitch3to1PhaseSupported	ONWAAR		
MaxChargingProfilesInstalled	60		
SupportedFileTransferProtocols	FTP		

Page **3** from **4**



Statement of Approval

Vendor		Date: 19-12-2019
Name	Vinoth Dayalan	Signature
Company	EVBox	
Department	Hardware	V.M
Position	Platform Integration Test Engineer	D.V.
Location	Amsterdam	1

Test laboratory		Date: 19-12-2019
Name	Ovidiu-Cristian Serban	Signature
Company	DNV GL Netherlands B.V.	
Department	Intelligent Networks & Communication	11-
Position	Senior Consultant	Aller
Location	Arnhem	V

Page **4** from **4**