

DATASHEET - FUSE-D03 100A T GL/GG 400VAC M30



Fuse-link, low voltage, 100 A, AC 400 V, 50 kA, D03, gL/gG, IEC, time-delay



Part no. FUSE-D03 100A T GL/GG 400VAC M30
Catalog No. 100NZ03

EL-Nummer (Norway) 1601253

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	100
Rated voltage			AC 400 V
Construction size			D03
Utilization category			gL/gG
Breaking Capacity		kA	50
usable for size/applications			for fuse-base M30 for domestic and general industrial applications
Release characteristic	class		time-delay
Standard/Approval			IEC
Shape			bottle
Standards/Regulations			IEC 60269-3 VDE 0636

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link (ecl@ss10.0.1-27-14-21-19 [ACN353011])			
Construction size			D03
Rated current		A	100
Rated voltage		V	400
Colour code			Red
Utilization category			gL/gG (cable protection/equipment protection)