



Fuse-link, medium voltage, 31.5 A, AC 24 kV, 50 kA, 2", 51 x 442 mm, back-up, DIN, with striker

Part no. 24KV 31.5Amp 2" DIN Resin Seal Fuse
Catalog No. 24TDMEJ31.5

EL-Nummer 2809021
(Norway)

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			medium voltage
Rated current	I	A	31.5
Rated voltage			AC 24 kV
Construction size			2"
Size			51 x 442 mm
Utilization category			back-up
Status indicator			with striker
Breaking Capacity		kA	50
usable for size/applications			transformer protection indoor or outdoor use
Standard/Approval			DIN
Standards/Regulations			DIN 43625 VDE 0670-4 VDE 0670-402 IEC 60282-1

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	31.5
Rated voltage		kV	24
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	50
Utilization category			Other
Application			Primary side transformer protection
Length		mm	442
Diameter		mm	51
Performance category according to IEC 60282-1			Back-up
With striker			Yes
Standard			DIN
Release characteristic			Other
Installation technique			Air