

3210063002

STATYS 1STAR 63 2W2P FX 220/240V



Strong points

- Standard features
- Alimentation
- Flexibility
- ATSM fonction
- Protection

General characteristics

- High reliability - internal redundant design to ensure service continuity.
- Flexibility and adaptability to various types of applications.
- Compact design: saves up to 40% of valuable space.
- Easy and secured maintenance.
- Operational security and ease of use. Remote data access in real time and from any location.
- Full support and service.

Compliance with standards

- IEC 62310
- IEC 60529
- AS 62310
- AS 60529
- IEC 62310-2
- AS 62310.2
- CE
- RCM

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/3210063002>

Static Transfer Systems (STS) are intelligent switches providing increased supply availability, automatically transferring loads to alternative power sources when the primary power source fails or is not available. They enable flexible site maintenance ensuring high availability.

Classification

| | |
|------------|----------|
| ETIM Class | EC002850 |
|------------|----------|

Commerce

| | |
|----------------------------|--|
| Description (240 char.) | STATYS PACK 63A 220/240V SINGLE PHASE 2 WIRES 2 POLE SWITCHING 19 INCHES RACK PC CLASS WITHOUT FUSES |
| Effective date | 2008-11-16 |
| Country of origin | FR |
| Discount Policy | D51 |
| Discount Policy Label | STATYS 32-100A |
| Length of the product unit | 0.089 |
| Width of the product unit | 0.483 |
| Depth of the product unit | 0.747 |
| Weight | 25 |

ETIM

| | |
|------------------------------|-------|
| Type of accessory/spare part | Other |
|------------------------------|-------|

Logistics

| | |
|----------------------------|---------------|
| GTIN/EAN | 3596032108052 |
| Customs number | 8536500500 |
| Weight of the packing unit | 25 |
| Length of the packing unit | 0.747 |
| Width of the packing unit | 0.483 |
| Depth of the packing unit | 0.089 |

Norms

| | |
|-------------------------|-----|
| Conformity to standards | IEC |
|-------------------------|-----|

Technical Characteristics

| | |
|-----------------|--------|
| Depth | 747 |
| Height | 89 |
| In/out | 1/1 |
| Number of poles | 2 |
| Output voltage | 230 |
| Rated frequency | 50/50 |
| Rated current | 63 |
| Width | 483 |
| Input voltage | 230 |
| Rate (min) | 63 |
| Rate (max) | 63 |
| LTM Protection | NoFuse |
| Switching Poles | 2P |