



**Fuse-link, high speed, 355 A, AC 240 V, DC 150 V, 200 kA, BS88, 38 x 84 mm, aR, BS**



**Part no. 355AMP 240V AC BS88 FUSE**  
**Catalog No. 355LMT**

## Delivery program

|                              |   |    |                                                                                                  |
|------------------------------|---|----|--------------------------------------------------------------------------------------------------|
| Product range                |   |    | Fuse                                                                                             |
| Basic function               |   |    | Fuse-link                                                                                        |
| Field of application         |   |    | high speed                                                                                       |
| Rated current                | I | A  | 355                                                                                              |
| Rated voltage                |   |    | AC 240 V<br>DC 150 V                                                                             |
| Construction size            |   |    | BS88                                                                                             |
| Size                         |   |    | 38 x 84 mm                                                                                       |
| Utilization category         |   |    | aR                                                                                               |
| Breaking Capacity            |   | kA | 200                                                                                              |
| usable for size/applications |   |    | protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters |
| Standard/Approval            |   |    | BS                                                                                               |
| Shape                        |   |    | offset bolted tags                                                                               |
| Standards/Regulations        |   |    | BS88-4<br>IEC 60269-4                                                                            |
| Optional accessories         |   |    | fuse-holder BH-0111                                                                              |

## Technical data ETIM 7.0

|                                                                                                                                                                                     |  |    |       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|-------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)                                                                                                             |  |    |       |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecI@ss10.0.1-27-14-20-05 [AFZ800015]) |  |    |       |
| Construction size                                                                                                                                                                   |  |    | Other |
| Rated current                                                                                                                                                                       |  | A  | 355   |
| Rated voltage                                                                                                                                                                       |  | V  | 240   |
| Voltage type                                                                                                                                                                        |  |    | AC/DC |
| Rated switching capacity                                                                                                                                                            |  | kA | 200   |
| Utilization category                                                                                                                                                                |  |    | Other |
| Type of fuse status indicator                                                                                                                                                       |  |    | None  |
| Insulated metal gripping lugs (IMGL)                                                                                                                                                |  |    | No    |