

DATASHEET - NH FUSE 400AMP 500V GG SIZE 3 DUAL IND



Fuse-link, low voltage, 400 A, AC 500 V, 120 kA, NH3, gL/gG, IEC, dual indicator, live gripping lugs



Part no. **NH FUSE 400AMP 500V gG SIZE 3 DUAL IND**
Catalog No. **400NHG3B**

EL-Nummer **1664084**
(Norway)

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	400
Rated voltage			AC 500 V
Construction size			NH3
Utilization category			gL/gG
Status indicator			dual indicator
Description			live gripping lugs
Breaking Capacity		kA	120
usable for size/applications			industrial
Standard/Approval			IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-2 fuse system A DIN 43620 VDE 0636-2
Optional accessories			fuse-holder SD3-D

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 (AFZ800015))			
Construction size			NH3
Rated current		A	400
Rated voltage		V	500
Voltage type			AC
Rated switching capacity		kA	120
Utilization category			gL/gG (cable protection/equipment protection)
Type of fuse status indicator			Combination fuse status indicator
Insulated metal gripping lugs (IMGL)			No