

DATASHEET - CYLINDRICAL FUSE 22 X 58 16A AM 690V AC



Fuse-link, low voltage, 16 A, AC 690 V, 80 kA, 22 x 58 mm, aM, IEC

Part no. **CYLINDRICAL FUSE 22 x 58 16A AM 690V AC**
Catalog No. **C22M16**

EL-Nummer
(Norway) **1600227**



Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	16
Rated voltage			AC 690 V
Size			22 x 58 mm
Utilization category			aM
Breaking Capacity		kA	80
usable for size/applications			motor protection for industrial applications
Standard/Approval			IEC
Shape			cylindrical
Standards/Regulations			IEC 60269-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			22x58 mm
Rated voltage		V	690 - 690
Rated voltage			Other
Voltage type			AC
Utilization category			aM (switchgear protection)
Rated operating frequency		Hz	45 - 62
Nominal current		A	16
With striker			No
Release characteristic			Other
Breaking capacity		kA	80