



Alarm contact 1C+1O 6A 240V AC

MZ202



Main electrical features	
Rated operational voltage Ue	230 / 415 V
Voltage	
Rated insulation voltage	4000 V
Max operating voltage	240 V
Rated operational voltage in DC	12 / 250 V
Electric current	
Acceptable current rating with AC1	6 A
Imin=f(U=12V DC) for power circuit	0,3 A
Imin = f (U = 230 V DC)	0,6 A
Imin=f(U=400V AC) for power circuit	3 A
Power	
Total power loss under IN	0,2 W
Endurance	
Electric endurance in number of cycles	6000
Number of mechanical operations	12000
Dimensions	
Depth of installed product	68 mm
Width of installed product	9 mm
Installation, mounting	
Tightening torque	1,3Nm
Factory fitted	no
360° product mounting position	yes
Connection	
Connection cross-sect. flexible conductor	6mm ²
Connection cross-sect. rigid cable	10mm ²
Type of contacts	1NC+1NO
Type of connection	with screw

Equipment

Quantity of NC contacts	1
Quantity of NO contacts	1

Standards

European directive WEEE	concerned
-------------------------	-----------

Use conditions

Operating temperature	-25 60 °C
Air humidity protection	95% / 80°C
Storage/transport temperature	-40 80 °C