



Fuse-link, high speed, 20 A, AC 690 V, 200 kA, 22 x 58 mm, gR, UL, IEC, with striker



Part no.
Catalog No.

Fuse 20A 690VAC gR 22x58 with Ind
FWP-20G22FI

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	20
Rated voltage			AC 690 V
Size			22 x 58 mm
Utilization category			gR
Status indicator			with striker
Breaking Capacity		kA	200
usable for size/applications			protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL IEC
Standards/Regulations			UL Recognized IEC Rated

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			22x58 mm
Rated voltage		V	690 - 690
Rated voltage			Other
Voltage type			AC
Utilization category			gR (general purpose semiconductor protection)
Rated operating frequency		Hz	45 - 62
Nominal current		A	20
With striker			Yes
Release characteristic			Other
Breaking capacity		kA	200