

# DATASHEET - FUSE 25A 690VAC GR 14X51 WITH IND



Fuse-link, high speed, 25 A, AC 690 V, 200 kA, 14 x 51 mm, gR, IEC, UL, with striker



Part no.  
Catalog No.

Fuse 25A 690VAC gR 14x51 with Ind  
FWP-25G14FI

## Delivery program

|                              |   |    |                                                                                                  |
|------------------------------|---|----|--------------------------------------------------------------------------------------------------|
| Product range                |   |    | Fuse                                                                                             |
| Basic function               |   |    | Fuse-link                                                                                        |
| Field of application         |   |    | high speed                                                                                       |
| Rated current                | I | A  | 25                                                                                               |
| Rated voltage                |   |    | AC 690 V                                                                                         |
| Size                         |   |    | 14 x 51 mm                                                                                       |
| Utilization category         |   |    | gR                                                                                               |
| Status indicator             |   |    | with striker                                                                                     |
| Breaking Capacity            |   | kA | 200                                                                                              |
| usable for size/applications |   |    | protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters |
| Standard/Approval            |   |    | IEC<br>UL                                                                                        |
| Shape                        |   |    | cylindrical                                                                                      |
| Standards/Regulations        |   |    | IEC 60269-4<br>UL 248-13                                                                         |

## Technical data ETIM 7.0

|                                                                                                                                                                                               |  |    |                                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|-----------------------------------------------|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)                                                                                                                           |  |    |                                               |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013]) |  |    |                                               |
| Size                                                                                                                                                                                          |  |    | 14x51 mm                                      |
| Rated voltage                                                                                                                                                                                 |  | V  | 690 - 690                                     |
| Rated voltage                                                                                                                                                                                 |  |    | Other                                         |
| Voltage type                                                                                                                                                                                  |  |    | AC                                            |
| Utilization category                                                                                                                                                                          |  |    | gR (general purpose semiconductor protection) |
| Rated operating frequency                                                                                                                                                                     |  | Hz | 45 - 62                                       |
| Nominal current                                                                                                                                                                               |  | A  | 25                                            |
| With striker                                                                                                                                                                                  |  |    | Yes                                           |
| Release characteristic                                                                                                                                                                        |  |    | Other                                         |
| Breaking capacity                                                                                                                                                                             |  | kA | 200                                           |