



Fuse-link, high speed, 4 A, AC 690 V, 200 kA, 10 x 38, gR, IEC, UL

Part no.
Catalog No.

Fuse 4A 690VAC gR 10x38
FWP-4G10F



Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	4
Rated voltage			AC 690 V
Size			10 x 38
Utilization category			gR
Breaking Capacity		kA	200
usable for size/applications			protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			IEC UL
Shape			cylindrical
Standards/Regulations			IEC 60269-4 UL 248-13

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			10x38 mm
Rated voltage		V	690 - 690
Rated voltage			Other
Voltage type			AC
Utilization category			gR (general purpose semiconductor protection)
Rated operating frequency		Hz	45 - 62
Nominal current		A	4
With striker			No
Release characteristic			Other
Breaking capacity		kA	200