

DATASHEET - 5AMP 700V AC 14 X 51MM FERRULE



Fuse-link, high speed, 5 A, AC 700 V, 200 kA, 14 x 51 mm, aR, UL

Part no. **5AMP 700V ac 14 X 51MM FERRULE**
Catalog No. **FWP-5A14F**



Delivery program

| | | | |
|------------------------------|---|----|--|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 5 |
| Rated voltage | | | AC 700 V |
| Size | | | 14 x 51 mm |
| Utilization category | | | aR |
| Breaking Capacity | | kA | 200 |
| usable for size/applications | | | protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters |
| Standard/Approval | | | UL |
| Shape | | | cylindrical |
| Standards/Regulations | | | UL 248 |
| Optional accessories | | | fuse-holder CH141B |

Technical data ETIM 7.0

| | | | |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013]) | | | |
| Size | | | 14x51 mm |
| Rated voltage | | V | 700 - 700 |
| Rated voltage | | | Other |
| Voltage type | | | AC/DC |
| Utilization category | | | aR (accompanied semiconductor protection) |
| Rated operating frequency | | Hz | 45 - 62 |
| Nominal current | | A | 5 |
| With striker | | | No |
| Release characteristic | | | Other |
| Breaking capacity | | kA | 200 |