

ITY3-TW030B

ITYS 3000VA VFI UPS 1/1 PF=1 WITH BATTERY INTEGRATED



Compact tower UPS system saves space in the operating environment.

Strong points

- Robust and easy to install
- High protection and availability
- Certified product
- Wide battery configurability

General characteristics

- Embedded dry-contact interface.
- Input mains switch breaker.
- Connection for battery extension modules.
- Power off the UPS remotely.
- Internal temperature sensor.

Compliance with standards

- IEC 62040-1
- IEC 62040-2
- IEC 62040-3
- RCM (E2376)

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/ITY3-TW030B>

Classification

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

Commerce

Description (240 char.)	ITYS 3000VA VFI UPS 1/1 PF=1 WITH BATTERY INTEGRATED
Effective date	2021-02-08
Country of origin	CN
Discount Policy	D05
Discount Policy Label	ITYS2
Weight	26

ETIM

Width	192
Height	322
Depth	428
Weight	26
Voltage type	AC
Bridging time full load	6
Suitable for network-management	Yes
Construction type	Free standing model
USB interface	Yes
Potential free switch contact	Yes
Input voltage	160..300
Output voltage	200..240
SNMP	Yes
USV- technology	Online
Primary frequency	40..70
Secondary frequency	50..60
Number of phases secondary	1
Number of phases primary	1
Auto shut down function	Yes
Max. voltage distortion output (linear load)	1
Output power factor	1
Overall efficiency	93
Efficiency in eco-mode	98
Input connection	C20
Number of output connections C13	8
Number of output connections C19	1
Output effective power	3000
Output apparent power	3000

Logistics

GTIN/EAN	8027122745963
Customs number	8504409590

Technical Characteristics

Depth	428
-------	-----

Height	322
In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	192
Sn	3
Pn	3
Conf	C1
Input voltage	230
Rate (min)	3
Rate (max)	3
Life Time	03-05
Typical Backup Time	9
Configuration	UPS Single Unit(s) with Bypass