

ITY3-TW108B

ITYS 8500VA VFI UPS 3/1 OR 1/1 PF=1



Compact tower UPS system saves space in the operating environment.

Strong points

- Robust and easy to install
- High protection and availability
- Certified product
- Wide battery configurability

General characteristics

- Embedded dry-contact interface.
- Input mains switch breaker.
- Connection for battery extension modules.
- Power off the UPS remotely.
- Internal temperature sensor.

Compliance with standards

- IEC 62040-1
- IEC 62040-2
- IEC 62040-3
- RCM (E2376)

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/ITY3-TW108B>

Classification

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

Commerce

Description (240 char.)	ITYS 8500VA VFI UPS X/1 PF=1 WITH BATTERY AND MANUAL BYPASS INTEGRATED
Effective date	2021-02-15
Country of origin	CN
Discount Policy	D05
Discount Policy Label	ITYS2
Weight	58

ETIM

Width	225
Height	589
Depth	416
Weight	58
Voltage type	AC
Bridging time full load	5.8
Suitable for network-management	Yes
Construction type	Free standing model
USB interface	Yes
Potential free switch contact	Yes
Input voltage	160..276
Output voltage	220..240
SNMP	Yes
USV- technology	Online
Primary frequency	40..70
Secondary frequency	50..60
Number of phases secondary	1
Number of phases primary	3
Auto shut down function	Yes
Max. voltage distortion output (linear load)	1
Output power factor	1
Overall efficiency	95
Efficiency in eco-mode	98
Input connection	Fixed connection
Number of output connections fixed connection	1
Output effective power	8500
Output apparent power	8500

Logistics

GTIN/EAN	8027122751254
Customs number	8504409590

Technical Characteristics

Depth	416
Height	589

In/out	3/1
Output voltage	230
Rated frequency	50/50
Width	225
Sn	8.5
Pn	8.5
Conf	C1
Input voltage	400
Rate (min)	8.5
Rate (max)	8.5
Life Time	03-05
Typical Backup Time	9
Configuration	UPS Single Unit(s) with Bypass