


Aluminium tehalit.queraz

Trunking for installation

tehalit.queraz trunking for installation in aluminium is ideal for electrical equipments in commercial premises.



Your benefits:

- Compatible with all the sockets 45 x 45 of the market.
- Lots of accessories and adjustable corners for a perfect fitting.
- Upper part is curved or flat and can be mounted as plinth or apron, horizontally or vertically.

Technical characteristics:

- 4 sizes in aluminium (54 x 54 to 56 x 162 mm).
- 13 accessories ensure mechanical protection continuity for all the circuit (IP40) according to NF C 15-100.
- Available in several colours: anodized aluminium or white lacquered (aluminium).

Expert tips

1



A complete range 1 to 3 compartments, aluminium.

2



Pre-cut partitions
Partitions are pre-cut to ease wiring.

3



High capacity
Profiles are designed for a higher capacity wiring in a compact space.

4






Handy accessories
Adjustable partition (from size 56 x 85 mm).

5



Trunking adapted socket outlets
systo special trunking was developed for direct fixing.









tehalit.queraz alu: aluminium trunking for installation

With direct snap-in system

Delivery information: Base and lid to be ordered separately (lid opening with screwdriver).



Standard length: 2 m. Other length on demand, max. 6 m.

Material: Profiles in natural anodized aluminum. Accessories in rigid PVC aluminium lacquered. Protection category: IP40, IK07.



	Base	Lid	Partition	Adjustable internal corner 83° to 97°	Adjustable external corner 83° to 140°
- Trunking volume and dimensions, see page J.31 - Cross section and diameter of cables, see page J.28 - Accessories dimensions, see page J.33					
	Cat. ref.	Cat. ref.	Cat. ref.	Cat. ref.	Cat. ref.
	natural anodized pure white black	GBA500501ALU GBA5005019010	GBA452ALU GBA4529010		
	packaging	24 m	24 m	L4369 72 m	
	natural anodized pure white black	GBA500851ALU GBA5008519010	GBA452ALU GBA4529010	L4471ALU L44719010	L4472ALU L44729010
	packaging	12 m	24 m	L4369 72 m	5 pieces 5 pieces
	natural anodized pure white black	GBA501311ALU GBA5013119010	GBA452ALU GBA4529010	L4391ALU L43919010	L4392ALU L43929010
	packaging	12 m	24 m	L4369 72 m	5 pieces 5 pieces
	natural anodized pure white	GBA501611ALU GBA5016119010	GBA452ALU GBA4529010	L4341ALU L43419010	L4342ALU L43429010
	packaging	8 m	24 m	4 pieces	4 pieces

	Description	Characteristics	Pack qty.	Colour	Cat. ref.
	Ground/wall junction joint		30m	pure white (9010)	L5071
L4770					
	Vertical support frame 45 x 45 mm		5		L4770
	Pack of 250 polyamide screws	L = 23 mm, Ø = 6 mm for fixing in BA13 type hollow partition	4		AFVISTC6023
	Earth terminal	material: steel	10		L4187CHRO
AFVISTC6023					
	Locking piece	use only for 22,5x45 or 45x45 mm module installation do not suit to central compartment GBD/A50161	30	pure white (9010) black (9011) alu (ALU)	L4389 L43899011 L4389ALU
L4389					

Colour:  natural anodized (ALU)
 pure white (9010)

Flat corner	End cap	Junction coupling piece
		
Cat. ref.	Cat. ref.	Cat. ref.
	L4433ALU L44339010	
	5 pieces	
L4478ALU L44789010	L4473ALU L44739010	L4467VERZ
4 pieces	5 pieces	2 pieces
L4398ALU L43989010	L4393ALU L43939010	L4467VERZ
4 pieces	5 pieces	2 pieces
L4348ALU L43489010	L4343ALU L43439010	L4467VERZ
2 pieces	5 pieces	2 pieces

Installation trunking

	Description	Characteristics	Pack qty.	Cat. ref.
 L5802	Base and lid earthing kit Accessories: 25 base terminals and 25 lid terminals	material: steel	1	L5802
 L4183	Earth strap	length 150 mm	25	L4181GNGE
		length 300 mm	25	L4182GNGE
		length 600 mm	25	L4183GNGE