

## NRT3-9000K

# NETYS RT 9KVA 230VAC+BAT



### Strong points

- Simple to install
- High protection and availability
- Certified performance
- Easy to use
- Extended and flexible back-up time

### General characteristics

- Rail kit.
- Embedded dry-contact interface (5000-11000 VA).
- Input mains switch breaker (5000-11000 VA).
- Connection for battery extension modules.
- Port for parallel operation (5000-11000 VA).
- Power off the UPS remotely.
- Internal temperature sensor.

### Compliance with standards

- IEC 62040-1
- IEC 62040-2
- IEC 62040-3
- AS 62040.1.1
- AS 62040.1.2
- AS 62040.2
- RCM (E2376)

### Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/NRT3-9000K>

Complete and professional, NETYS RT is a single-phase rack-tower UPS ensuring protection and availability of IT infrastructure that meet both requirements of power reliability and installation flexibility.

### Classification

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

### Commerce

Description (240 char.)	NeTYS RT 9000VA/8000W VFI UPS 1/1 WITH BATTERY INTEGRATED +RAILS
Effective date	2021-04-01
Country of origin	IT
Discount Policy	D04
Discount Policy Label	NETYS RT
Weight	83

### ETIM

Width	440
Height	220
Depth	650
Weight	83
Voltage type	AC
Bridging time full load	9.3
Suitable for network-management	Yes
Construction type	482.6 mm (19 inch) device
USB interface	Yes
Potential free switch contact	Yes
Input voltage	175..280
Output voltage	200..240
SNMP	Yes
USV- technology	Online
Primary frequency	40..70
Secondary frequency	50..60
Number of phases secondary	1
Number of phases primary	1
Auto shut down function	Yes
Max. voltage distortion output (linear load)	2
Output power factor	0.89
Overall efficiency	95.5
Efficiency in eco-mode	98
Input connection	Fixed connection
Number of output connections fixed connection	1
Output effective power	8000
Output apparent power	9000

### Logistics

GTIN/EAN	8027122754804
Customs number	8504409590

### Norms

Conformity to standards	IEC
-------------------------	-----

**Technical Characteristics**

Depth	650
Height	220
In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	440
Sn	9
Pn	8
Conf	C1
Input voltage	230
Rate (min)	9
Rate (max)	9
Life Time	03-05
Typical Backup Time	11
Configuration	UPS Single Unit(s) with Bypass